

Vehicle-No.: 405020



Mercedes-Benz 1527 K ATEGO tipper

Euro 97.500,00 + Mwst.

AVG Trucks GmbH

Gwinnerstraße 36

60388 Frankfurt/M

Telephone: **+49 (0) 69-942138-0**

Fax: **+49 (0) 69-942138-38**

info@avg-trucks.de

<http://www.avg-trucks.de>

Contract structure	loading crane Palfinger PK 9.501 SLD B, Flur- und Funkfernsteuerung, Drehkopf mit Zweischalengreifer. Diagramm: 5,6 m - 1.420 kg, 7,5 m - 1.020 kg, 9,6 m - 780 kg. full service history
First registration	03.11.2020
Mileage	27.400 km
Clearance store room dimensions	4000 x 2350 x 500 mm
Emission level	6
Engine power	200/272 kW/PS
Total weight	16.000 kg
Kerb weight	8.300 kg
Payload	7.700 kg
Wheelbase	3.260 mm
Suspension	parabolic springs
Operator's cab	short

Equipment

A1L Front axle 6.1 t

A2L Rear axle, ring gear 390, hyoid, 11 t

A2Z Differential lock rear axle

B1B Electronic braking system with ABS and ASR

B2C Disc brakes at front, drum brakes on rear axle

C1L Wheelbase 3260 mm

C6S Stabilizer, for extreme high load, rear axle

D1C Driver's suspension seat comfort

D4B Classical cockpit

D4W Window lifters, electrically on both sides

D6F Air conditioning

D8A Roof hatch / vent, roof

E6Z Reversing alarm

F07 "S" cab, short version

F1P short cab

F1X S-driver ClassicSpace 2.30 m, tunnel

F2U ClassicSpace

F4I Driver's back, with window

F5L Sun visor, exterior, transparent

F68 Rearview mirror electrically adjustable and heatable

F8L Immobilizer

F8X Rain / light sensor

G0V Driving program power

G1E Gearbox G 140-8 / 9.30-0.79

G40 Automatic transmission

G5G Mercedes PowerShift 3

H16 Driver's seat heating

I4A 4x2 wheel formula

I6W Steel suspension, Rear Axle

J1C Instrument cluster, 12.7 cm, video function

J3N FleetBoard Eco Support
J5S Radio, with USB port and Bluetooth
J9D Pre-installation for toll collection
J9N Preparation for Truck Data Center 6 (DTCO)
K0E Tank 120 liters
K3T AdBlue tank 25 liters
L1C LED-daytime running lights
L1Y LED light package at the front, with white flashing glasses
L2L Rotating beacon, yellow
M0U Soundproofing, special package
M2C Motor OM936, R6, 7,7 l, 200 kW (272 PS), 1100 Nm
M5C Engine version Euro 6, D
M5V High Performance Engine Brake
N2I NA MB 121-2c, Pumpe
N8J Meiller pump, 7-piston, type 270/63
P29 Platform front panel extension
P50 Three-side dumping mechanism
PZ0 Anchorage points in loading platform
PZ6 Loading certificate DIN EN 12642 Code XL
Q1I Front spring, 6.1 t, parabola
Q2H Rear spring, 10.5 t, parabolic
S1D Stability Rules Wizard
S1H Lane keeping assistant
S1P Active Brake Assist
S5Z cruise control
T3A Weight variant 16.0 t (6.1 / 10.5)
Y22 Tool chest
Z4E Engine 6-cylinder
Z5M PTO, simply
Z99 Vehicle without sparewheel

Legal notice: The details of this offer are subject to change.
Subject to prior sale. For sale to businesses only.