

Vehicle-No.: 503022


Mercedes-Benz 3253 L AROCS 8X4 aspirator

Euro 558.000,00 + Mwst.
AVG Trucks GmbH

Gwinnerstraße 36

60388 Frankfurt/M

 Telephone: **+49 (0) 69-942138-0**

 Fax: **+49 (0) 69-942138-38**
info@avg-trucks.de
<http://www.avg-trucks.de>

| | |
|--------------------|---|
| Contract structure | Caster steering axle entlast- und liftbar. full service history |
| First registration | 26.01.2023 |
| Mileage | 16.200 km |
| Emission level | 6 |
| Engine power | 390/530 kW/PS |
| Total weight | 32.000 kg |
| Kerb weight | 28.285 kg |
| Payload | 3.715 kg |
| Wheelbase | 4.200 mm |
| Suspension | parabolic/air |
| Operator's cab | cab medium length |

Equipment

| |
|--|
| A1E Front axle 9,0 t |
| A1Y Front axle, straight version |
| A2G Rear axle, crown wheel 300, planets, 13.4 t |
| A4Q Trailing axle, 9 t, steered, can be relieved, lifted |
| A6A Final drive ratio i = 4.571 |
| B1B Electronic braking system with ABS and ASR |
| B2A Disk-brakes front- and rearaxle |
| B2X Parking brake, electronic |
| C2I Wheelbase 4200 mm |
| C6Q Anti roll bar front |
| D0A leather Steering Wheel |
| D1C Driver's suspension seat comfort |
| D1N Passenger seat feature |
| D4Z Sun blind side, driver and passenger side |
| D6F Air conditioning |
| D6I Residual heat |
| D6M Hot water heater, cab |
| D8A Roof hatch / vent, roof |
| E4B Interface, fleet management system FMS |
| E4W Traction, speed limit 30 km / h |
| E6A Trailer socket 24V, 15-pin |
| E6Y Reversing alarms combined with hazard lights |
| E7F Cable remote control for air suspension |
| E9G Preparation for electrical devices |
| F05 "M" cab, of medium length |
| F1B M-Cab Classic Space 2,30 m, tunnel 170 mm |
| F1Q Medium sized cab |
| F2B Floor variant, tunnel 170 mm |
| F2G Cabin width 2.30 m |
| F2N Cab, 600 mm heel height |
| F2U ClassicSpace |

| |
|--|
| F4X Storage compartment outside flap left |
| F5L Sun visor, exterior, transparent |
| F6Q Air horn |
| F6T MirrorCam |
| F7D Bumper, middle part towing eyes, coupling jaw |
| F7Y Cab access left / right to move |
| F8E Locking system with central locking |
| F8F comfort Lock |
| F8V Light sensor |
| F8W Rain sensor |
| G0K Driving program economy / power |
| G0T Predictive Powertrain Control (PPC) |
| G40 Automatic transmission |
| G5G Mercedes PowerShift 3 |
| H16 Driver's seat heating |
| I4R Wheel formula 8x4 ENA |
| I5G 32.0 ton truck |
| I6X Air suspension, rear axle |
| J2K Speaker, 2-way system |
| J2U Navigation system |
| J3U Requirement FleetBoard Manager App |
| J3V Truck Data Center 7 |
| J3Z Axle load measuring device |
| J6C Multimedia cockpit, interactive |
| J9D Pre-installation for toll collection |
| J9P Pre-equipment and display for up to 4 cameras |
| K1L Tank 430 liters |
| K3V AdBlue tank 60 liters |
| L1A Bi-Xenon headlights |
| L1I Fog lights, LED - Daytime running lights |
| L2R 2 LED all-round beacons |
| L3Z Headlight washers |
| M3E Motor OM471, R6, 12.8 l, 390 kW (530 hp) 2600 Nm |
| M4X Engine version Euro 6, E |
| M5B 2nd generation engine OM471 |
| M5V High Performance Engine Brake |
| N4Z |
| N6L |
| N6Z Transmission oil cooling |
| N7M Motor output back, c, hydraulicpump ISO 7653D |
| O1T Interior color greige/anthracite |
| Q1Y Front spring 9.0t, 4-leaf |
| Q3Z Frame lowering, bellows residual pressure control |
| Q8D Tow hitch, rear, ring spring |
| Q8R Crossbeam, reinforced |
| R2Y Alloy Rims 9:00 X 22.5 |
| R5E Alloy Rims 11.75 X 22.5, VA |
| R5H Alloy Rims 11.75 X 22.5, NLA |
| S5Z cruise control |
| U1W AdBlue pipes, water-heated |
| W7K Weight variant 37.0 t (9.0/10.5/10.5/8.0) |
| X3Z ATS warranty according to AGB, 3 years / 250000 km |
| Y1W Refrigerator, on motor tunnel |
| Y2I Storage box |
| Z1H EBS |

Z99 Vehicle without sparewheel

Legal notice: The details of this offer are subject to change.
Subject to prior sale. For sale to businesses only.

© 2005 **AVG** Trucks GmbH