

Vehicle-No.: 605010



Mercedes-Benz 2546 L ACTROS platform with tarpaulin

Euro 73.500,00 + Mwst.

AVG Trucks GmbH

Gwinnerstraße 36

60388 Frankfurt/M

Telephone: **+49 (0) 69-942138-0**

Fax: **+49 (0) 69-942138-38**

info@avg-trucks.de

<http://www.avg-trucks.de>

Contract structure	tail-lift Bär 2.000 kg, 2.000 mm. full service history
First registration	03.02.2021
Mileage	259.400 km
Clearance store room dimensions	7200 x 2470 x 2360 mm
Emission level	6
Engine power	335/456 kW/PS
Total weight	26.000 kg
Kerb weight	9.800 kg
Payload	16.200 kg
Wheelbase	4.600 mm
Suspension	Air suspension
Operator's cab	cab medium length

Equipment

1G2 12-gear transmission automatic
1WP Sliding tarpaulin frame
2P0 Sliding side-panel of tarpaulin on left and right
A1A Front axle with air suspension
A1D Front axle 8.0 t
A4Z Trailing axle, fit to be raised, 7,5 t
B1B Electronic braking system with ABS and ASR
B2A Disk-brakes front- and rear axle
B2X Parking brake, electronic
B5A Trailer brake, 2-line connections left
C2P Wheelbase 4.600 mm
D1C Driver's suspension seat comfort
D1N Passenger seat feature
D6G automatic climate control
D6I Residual heat
D7Q Storage, high, on the engine tunnel
D8A Roof hatch / vent, roof
E3Q Additional socket 24 V / 15 A, passenger's footwell
E4B Interface, fleet management system FMS
E4W Traction, speed limit 30 km / h
E6A Trailer socket 24V, 15-pin
E6Y Reversing alarms combined with hazard lights
E7F Cable remote control for air suspension
F1O M-Cab Classic Space 2,30 m, tunnel 320 mm
F1Q Medium sized cab
F2G Cabin width 2.30 m
F2M Cab, 420 mm height landing
F2U ClassicSpace
F4X Storage compartment outside flap left
F5A Air deflectors

F5L Sun visor, exterior, transparent

F6R Air horns, cab roof

F6T MirrorCam

F8E Locking system with central locking

F8F comfort Lock

F8V Light sensor

F8W Rain sensor

G0K Driving program economy / power

G0T Predictive Powertrain Control (PPC)

G5G Mercedes PowerShift 3

H16 Driver's seat heating

I4C Wheel formula 6x2 ENA

I6X Air suspension, rear axle

J2K Speaker, 2-way system

J2O Convenience telephony, wireless charging

J2U Navigation system

J3U Requirement FleetBoard Manager App

J3V Truck Data Center 7

J3Z Axle load measuring device

J6C Multimedia cockpit, interactive

J9D Pre-installation for toll collection

J9P Pre-equipment and display for up to 4 cameras

K1E Tank 390 liter

K3V AdBlue tank 60 liters

L1I Fog lights, LED - Daytime running lights

M2S Motor OM470, R6, 10,7 L, 335 kW (455 PS), 2200 Nm

M5A 2nd generation engine OM470

M5C Engine version Euro 6, D

M5V High Performance Engine Brake

P18 Board walls aluminum

P26 Roofing de-icing system

PZ0 Anchorage points in loading platform

PZ2 Loading certificate VDI 2700

PZ4 anchorage points in outer frame

PZ5 Outer frame hole

PZ6 Loading certificate DIN EN 12642 Code XL

Q7J Towbar Standard D40, Ringfeder

S1D Stability Rules Wizard

S1H Lane keeping assistant

S1L Alertness assistant

S1O Traffic sign assistant

S1R Blind Spot Assist

S1W Active Brake Assist 5

S5Z cruise control

S6F Sideguard Assist, permanently active

U1W AdBlue pipes, water-heated

V2F Actros S/M cab model generation 5

V42 Load securing rails

W2X Weight variant 26.0 t (8.0 / 11.5 / 7.5)

Y22 Tool chest

Z1H EBS

Z99 Vehicle without sparewheel

Legal notice: The details of this offer are subject to change.
Subject to prior sale. For sale to businesses only.